


## **Shed Roof Kit Fixing Guide**

Please note: This kit is designed for use with an 8ft x 6ft

Apex shed roof, check that each side of the roof has a size


of approx. 2.44m across and 1m up the roof.



Open and check contents.

There should be:

6 sheets 1m x 1.06m 2 ridge pieces 1 small ridge piece Pack of 100 Nails



If you are replacing the roof, check that the existing felt is not unduly wrinkled, smooth out any bumps.

Maximum possible useable dimensions are 2.546 x 1.10m



Start by placing one of the sheets to the left hand side of the building, allowing no more than a 20mm overhang.



Nail through the top of the corrugation into the existing boarding using the nails provided.



Place the next sheet onto the first with a two corrugation overlap and fix as before.



Fix the final sheet next to the second with the appropriate overlap and ensure that it aligns with the edge of your shed roof and then nail.

Repeat this procedure on the other side of the building starting again from the left.



Place the ridge pieces on the top of the roof and overlap to ensure they extend from one end to the other, if necessary covering any existing timber barge boards.



Nail along the ridge pieces through the corrugation tops to complete.



Onduline Building Products Ltd, Eardley House, 182-184 Campden Hill Road, London, W8 7AS

Tel: 0207 727 0533 Fax: 0207 792 1390

Email: enquiries@onduline.net